

The Icon EDGE is a very compact, feature rich, lightweight, fast beam/spot/wash luminaire. It combines an ultra-bright beam, with sharp gobo projection, a CMY-color mixing system and variable CTO. Fitted with the new Philips Platinum 21R lamp (470W), Icon EDGE outputs an amazing 20,000 Lumens.

Featuring 2-24 degree zoom in beam mode, and 2.5-32 degree zoom in spot mode, eight rotating gobos and 14 fixed, a continuous animation wheel and two prisms the Icon EDGE has a huge amount of creative options. A newly designed system provides extremely smooth, full field dimming.

The fixture can take direct Art-Net input, as well as DMX512. Icon EDGE is a multi-use luminaire, with full animation wheel, beam, spot and wash function in one fixture.



Philips Platinum 21R

Features:

20,000 Lumen output

Extremely narrow ACL beam with zoom

Even spot function

Large Zoom range

Full 16bit CMY + incl CTO

14 + Open fixed colour wheel

8 + Open interchangable rotating gobos

Custom glass gobo mode available

14 + Open fixed Gobo

Continuous animation wheel


2 Prisms (8 facet, linear 4 facet)

Split colours

Drop In frost

Ultra-fast Pan/Tilt movement

Can be mounted in any orientation



0	10m	20m	30m
Beam	390.000	110.000	55.000lux
Spot	120.000	26.000	16.000lux
Wash	84.000	25.000	10.000lux

Technical Specifications:

Lamp

Lamp		
Colour Temperature	7800K	
Beam Angle (beam)	2-24°	
Beam Angle (Spot)	2.5-32°	
Beam Angle (Wash)	3.5-39°	
Lumens Output	20.000	
Nominal Lifetime	750 hrs	
Focus	adjustable focus	
Frost	drop-in	
Colour wheel	14 + open	
CMY	0-100%/ 16bit	
СТО	0-100%/ 16bit	
Rotating Gobo	8+ open	
Indexing Gobo	yes	
Fixed Gobo	14+ open	
Prism	8 facet + lin 4 facet	
Indexing Prism	yes	
Animation Wheel	continuous	
Indexing Animation Wheel	yes	
Shutter/Strobe	variable, 13 flash/sec	
Dimmer	0-100%/ 16 bit	
Pan/Tilt	540/270°	
DMX Control Mode	2 (25, 37 CH)	
RDM	yes	
Art-Net	yes	
Self Charging Battery	yes	
Cooling System Monitoring	yes	
Wattage	650W	
Power	AC100-240V, 50/60hz	
Operating Temperature	-10° to +45°c	
Certification	CE & cETL	
Weight	31kg	
Dimensions LxWxH (mm)	453x319x709	



GOBO COLOR SHEETS:

